

MC70L

Running current

Casing					Colour	White
Dimensions	Unit	Height	mm		576	
		Width	mm		403	
		Depth	mm		241	
Weight	Unit	kg		8.5		
Applicable room area				m ²	46	
Air purifying operation	Power input	Turbo	kW		0.065	
		H	kW		0.026	
		M	kW		0.016	
		L	kW		0.01	
		Silent	kW		0.007	
Sound pressure level	Air purifying operation	Turbo	dBA		48	
		High	dBA		39	
		Medium	dBA		32	
		Low	dBA		24	
		Silent	dBA		16	
Fan	Air flow rate	Air purifying operation	Turbo	m ³ /h		420
			High	m ³ /h		285
			Medium	m ³ /h		210
			Low	m ³ /h		130
			Silent	m ³ /h		55
Dust collecting method					Plasma ionizer §§ Electrostatic dust collection filter	
Deodorizing method					Flash streamer §§ Titanium apatite photocatalytic filter §§ Deodorising catalyst	
Bacteria filtering method					Flash streamer §§ Titanium apatite photocatalytic filter	
Safety devices	Item	1		Safety switch (operation stops when the front panel opens)		
Standard Accessories	Item				Wireless remote control	
	Quantity				1	
	Item				Photocatalytic pleated Filter	
	Quantity				5	
	Item				Operation manual	
Quantity				1		
Power cord			m	2		
Power supply	Phase				1~	
	Frequency			Hz	50/60	
	Voltage			V	220-240/220-230	
Air purifying operation	Turbo		A	0.55		
	High		A	0.25		
	Medium		A	0.15		
	Low		A	0.1		

Notes		Sound power levels are the average of values measured at 1m away from the front, left, right and top of the unit (this is equal to the value in an anechoic chamber).
		Panel color: white; Display part color: silver